

Mirage oil free CS3

Type: **oil free traditional piston pump**

Transmission type: **direct**

Starting type: **direct drive**

Range of power: **3 Hp - 2,2 kW**

Range of pressure: **up to 7 Bar**

Oil residual (ISO 8573-1): **class 1**

F.A.D. (ISO 2017 annex C): **250 L/min**

Noise level: **max 66 L_{WA} (dB)**

Motor efficiency: **IE2**

Duty cycle: **S3 70%**














CS3-25/3



CS3-100/3

Mirage CS3 3 Hp 7 Bar

Oil free compressors

Model	 Pump Head	 Tank	 Air Displacement		 Free Air Delivery*		 Power Supply	 Nominal Power		 Revolutions	 Max Pressure		 Noise Level	 Dimensions	 Weight
MIRAGE	type	Lt.	L/min	CFM	L/min	CFM	V/Hz	HP	kW	Rpm	Bar	Psi	L _{WA} (dB)	mm	Kg
CS3-25/3	CS3	25	360	12,7	250	8,8	230/50	3	2,2	1450	7	102	66	510 x 600 x 830	49
CS3-100/3	CS3	100	360	12,7	250	8,8	230/50	3	2,2	1450	7	102	66	1200 x 500 x 750	80

*L/min at 5 Bar / CFM at 70 Psi

Dimension: Length x Depth x Height