



Base mounted with dryer IVR

Type: **oil injected**

Transmission type: **direct**

Starting type: **star-delta**

Range of power: **10÷75 Hp - 7,5÷15 kW**

Range of pressure: **8÷13 Bar**

Oil residual (ISO 8573-1): **≤ 3 (class 4)**

Max humidity (ISO 8573-1): **≤ 10°C (class 6)**

F.A.D. (ISO 2017 annex C): **830÷2330 L/min**

Noise level: **max 77 L_{WA} (dB)**

Motor efficiency: **up to IE3**



FIRE 10K-13E D IVR

FIRE IVR 10÷20 Hp 8-10-13 Bar

Model	Nominal Power		Tank	F.A.D. max		F.A.D. min		Power supply	Outlet BSP	Dryer	Max Pressure		Noise Level	Dimensions	Weight
FIRE	HP	kW	Lt.	L/min	CFM	L/min	CFM	V/Hz	connection	V/Hz	Bar	Psi	L _{WA} (dB)	mm	Kg
10K-8E D IVR	10	7,5	-	1215	42,9	300	10,6	400/50	G 1/2"	230/50	8	116	75	127 x 66 x 65	187
10K-10E D IVR	10	7,5	-	1050	37,1	300	10,6	400/50	G 1/2"	230/50	10	145	75	127 x 66 x 65	187
10K-13E D IVR	10	7,5	-	830	29,3	400	14,1	400/50	G 1/2"	230/50	13	188	75	127 x 66 x 65	187
15K-8E D IVR	15	11	-	1810	63,9	800	28,2	400/50	G 3/4"	230/50	8	116	75	148 x 78 x 82	252,5
15K-10E D IVR	15	11	-	1510	53,3	750	26,5	400/50	G 3/4"	230/50	10	145	75	148 x 78 x 82	252,5
15K-13E D IVR	15	11	-	1200	42,4	640	22,6	400/50	G 3/4"	230/50	13	188	75	148 x 78 x 82	252,5
20K-8E D IVR	20	15	-	2330	82,3	800	28,2	400/50	G 3/4"	230/50	8	116	77	148 x 78 x 82	262,5
20K-10E D IVR	20	15	-	2000	70,6	750	26,5	400/50	G 3/4"	230/50	10	145	77	148 x 78 x 82	262,5
20K-13E D IVR	20	15	-	1600	56,5	530	18,7	400/50	G 3/4"	230/50	13	188	77	148 x 78 x 82	262,5

Dimensions : Length x Depth x Height