



Base mounted with dryer

Type: **oil injected**

Transmission type: **belt**

Starting type: **star-delta**

Range of power: **5,5÷20 Hp - 4÷15 kW**

Range of pressure: **8÷13 Bar**

Oil residual (ISO 8573-1): **≤ 3 (class 4)**

Max humidity (ISO 8573-1): **≤ 10°C (class 6)**

F.A.D. (ISO 2017 annex C): **381÷2090 L/min**

Noise level: **max 68 L_{wa} (dB)**

Motor efficiency: **up to IE3**



FIRE 15K-13E

FIRE 5,5÷20 Hp 8-10-13 Bar

Model	Nominal Power		Tank		F.A.D.			Power supply	Outlet BSP	Dryer	Max Pressure		Noise Level	Dimensions	Weight
	HP	kW	Lt.	L/min	CFM	M3/h	V/Hz	connection	V/Hz	Bar	Psi	L _{wa} (dB)	mm	Kg	
5,5K-8E	5,5	4	-	550	19,4	33	400/50	G 1/2"	230/50	8	116	65	135 x 62 x 65	170,5	
5,5K-10E	5,5	4	-	490	17,3	29,4	400/50	G 1/2"	230/50	10	145	65	135 x 62 x 65	170,5	
5,5K-13E	5,5	4	-	381	13,5	22,9	400/50	G 1/2"	230/50	13	188	65	135 x 62 x 65	170,5	
7,5K-8E	7,5	5,5	-	805	28,4	48,3	400/50	G 1/2"	230/50	8	116	66	135 x 62 x 65	178,5	
7,5K-10E	7,5	5,5	-	690	24,4	41,4	400/50	G 1/2"	230/50	10	145	66	135 x 62 x 65	178,5	
7,5K-13E	7,5	5,5	-	561	19,8	33,7	400/50	G 1/2"	230/50	13	188	66	135 x 62 x 65	178,5	
10K-8E	10	7,5	-	1170	41,3	70,2	400/50	G 1/2"	230/50	8	116	67	135 x 62 x 65	179,5	
10K-10E	10	7,5	-	980	34,6	58,8	400/50	G 1/2"	230/50	10	145	67	135 x 62 x 65	179,5	
10K-13E	10	7,5	-	785	27,7	47,1	400/50	G 1/2"	230/50	13	188	67	135 x 62 x 65	179,5	
15K-8E	15	11	-	1610	56,8	96,6	400/50	G 3/4"	230/50	8	116	68	151 x 73 x 82	257,5	
15K-10E	15	11	-	1462	51,6	87,7	400/50	G 3/4"	230/50	10	145	68	151 x 73 x 82	257,5	
15K-13E	15	11	-	1166	41,2	70	400/50	G 3/4"	230/50	13	188	68	151 x 73 x 82	257,5	
20K-8E	20	15	-	2090	73,8	125,4	400/50	G 3/4"	230/50	8	116	68	151 x 73 x 82	269,5	
20K-10E	20	15	-	1990	70,3	119,4	400/50	G 3/4"	230/50	10	145	68	151 x 73 x 82	269,5	
20K-13E	20	15	-	1600	56,5	96	400/50	G 3/4"	230/50	13	188	68	151 x 73 x 82	269,5	

Dimensions : Length x Depth x Height