



Mirage oil free CS2

Type: **oil free traditional piston pump**
 Transmission type: **direct**
 Starting type: **direct drive**
 Range of power: **2 Hp - 1,5 kW**
 Range of pressure: **up to 7 Bar**

Oil residual (ISO 8573-1): **class 1**
 F.A.D. (ISO 2017 annex C): **170 L/min**
 Noise level: **max 66 L_{WA}(dB)**
 Motor efficiency: **IE2**
 Duty cycle: **S3 70%**



Mirage CS2 2 Hp 7 Bar

Oil free compressors

Model	Pump Head	Tank	Air Displacement		Free Air Delivery*		Power Supply	Nominal Power		Revolutions	Max Pressure		Noise Level	Dimensions	Weight
MIRAGE	type	Lt.	L/min	CFM	L/min	CFM	V/Hz	HP	kW	Rpm	Bar	Psi	L _{WA} (dB)	mm	Kg
CS2-25/2	CS2	25	240	8,5	170	6	230/50	2	1,5	1450	7	102	66	510 x 600 x 830	42
CS2-50/2	CS2	50	240	8,5	170	6	230/50	2	1,5	1450	7	102	66	950 x 400 x 600	45
CS2-50/2 SS	CS2	50	240	8,5	170	6	230/50	2	1,5	1450	7	102	56	950 x 450 x 830	49

*L/min at 5 Bar / CFM at 70 Psi
 SS = super silent

Dimension: Length x Depth x Height