

Stealth oil free BS2

Type: **oil free WOB-L piston pump**

Transmission type: **direct**

Starting type: **direct drive**

Range of power: **1,5 Hp - 1,1 kW**

Range of pressure: **up to 7 Bar**

Dew point (with membrane dryer): **-20 °C**

(with adsorption dryer): **-40 °C**

Oil residual (ISO 8573-1): **class 1**

F.A.D. (ISO 2017 annex C): **135 L/min**

Noise level: **max 66 L_{wa}(dB)**












Motor efficiency: **IE2**

Duty cycle: **S3 50%**



Stealth BS2 1,5 Hp 7 Bar

Oil free compressors

Model	 Pump Head	 Tank	 Air Displacement		 Free Air Delivery*		 Power Supply	 Nominal Power		 Revolutions	 Max Pressure		 Noise Level	 Dimensions	 Weight
STEALTH	type	Lt.	L/min	CFM	L/min	CFM	V/Hz	HP	kW	Rpm	Bar	Psi	L _{wa} (dB)	mm	Kg
BS2-24/1,5	BS2	24	182	6,4	135	4,8	230/50	1,5	1,1	1380	7	102	66	430 x 400 x 600	33
BS2-40/1,5	BS2	40	182	6,4	135	4,8	230/50	1,5	1,1	1380	7	102	66	600 x 410 x 770	38
BS2-40/1,5E	BS2	40	182	6,4	120	4,2	230/50	1,5	1,1	1380	7	102	66	710 x 410 x 770	42
BS2-40/1,5 SS	BS2	40	182	6,4	135	4,8	230/50	1,5	1,1	1380	7	102	56	600 x 460 x 890	42
BS2-40/1,5E SS	BS2	40	182	6,4	120	4,2	230/50	1,5	1,1	1380	7	102	56	710 x 460 x 890	46

*L/min at 5 Bar / CFM at 70 Psi
E = equipped with membrane dryer
SS = super silent

Dimension: Length x Depth x Height