



Base mounted

Type: **oil injected** Oil residual (ISO 8573-1): **≤ 3 (class 4)**
 Transmission type: **belt** F.A.D. (ISO 2017 annex C): **381 ÷ 8530 L/min**
 Starting type: **star-delta** Noise level: **max 70** L_{wa} (dB)
 Range of power: **5,5 ÷ 75 Hp - 4 ÷ 55 kW** Motor efficiency: **up to IE3**
 Range of pressure: **8 ÷ 13 Bar**



FIRE 5,5 ÷ 20 Hp 8-10-13 Bar

Model	Nominal Power		Tank	F.A.D.			Power supply	Outlet BSP	Dryer	Max Pressure		Noise Level	Dimensions	Weight
	HP	kW	Lt.	L/min	CFM	M3/h	V/Hz	connection	V/Hz	Bar	Psi	L_{wa} (dB)	mm	Kg
5,5K-8	5,5	4	-	550	19,4	33	400/50	G 1/2"	-	8	116	65	98 x 62 x 65	140
5,5K-10	5,5	4	-	490	17,3	29,4	400/50	G 1/2"	-	10	145	65	98 x 62 x 65	140
5,5K-13	5,5	4	-	381	13,5	22,9	400/50	G 1/2"	-	13	188	65	98 x 62 x 65	140
7,5K-8	7,5	5,5	-	805	28,4	48,3	400/50	G 1/2"	-	8	116	66	98 x 62 x 65	148
7,5K-10	7,5	5,5	-	690	24,4	41,4	400/50	G 1/2"	-	10	145	66	98 x 62 x 65	148
7,5K-13	7,5	5,5	-	561	19,8	33,7	400/50	G 1/2"	-	13	188	66	98 x 62 x 65	148
10K-8	10	7,5	-	1170	41,3	70,2	400/50	G 1/2"	-	8	116	67	98 x 62 x 65	148
10K-10	10	7,5	-	980	34,6	58,8	400/50	G 1/2"	-	10	145	67	98 x 62 x 65	148
10K-13	10	7,5	-	785	27,7	47,1	400/50	G 1/2"	-	13	188	67	98 x 62 x 65	148
15K-8	15	11	-	1610	56,8	96,6	400/50	G 3/4"	-	8	116	68	116 x 74 x 82	224
15K-10	15	11	-	1462	51,6	87,7	400/50	G 3/4"	-	10	145	68	116 x 74 x 82	224
15K-13	15	11	-	1166	41,2	70	400/50	G 3/4"	-	13	188	68	116 x 74 x 82	224
20K-8	20	15	-	2090	73,8	125,4	400/50	G 3/4"	-	8	116	68	116 x 74 x 82	234
20K-10	20	15	-	1990	70,3	119,4	400/50	G 3/4"	-	10	145	68	116 x 74 x 82	234
20K-13	20	15	-	1600	56,5	96	400/50	G 3/4"	-	13	188	68	116 x 74 x 82	234

Dimensions : Length x Depth x Height

FIRE 75K-10



FIRE 25÷75 Hp 8-10-13 Bar

Model	Nominal Power		Tank		F.A.D.		Power supply	Outlet BSP	Dryer	Max Pressure		Noise Level	Dimensions	Weight
	HP	kW	Lt.	L/min	CFM	M3/h	V/Hz	connection	V/Hz	Bar	Psi	L _{max} (dB)	mm	Kg
25K-8	25	18,5	-	2880	102,8	174,6	400/50	G 1 1/4"	-	8	116	66	106 x 86 x 124	458
25K-10	25	18,5	-	2540	89,7	152,4	400/50	G 1 1/4"	-	10	145	66	106 x 86 x 124	458
25K-13	25	18,5	-	1920	67,8	115,2	400/50	G 1 1/4"	-	13	188	66	106 x 86 x 124	458
30K-8	30	22	-	3440	121,5	206,4	400/50	G 1 1/4"	-	8	116	66	106 x 86 x 124	495
30K-10	30	22	-	3020	106,6	181,2	400/50	G 1 1/4"	-	10	145	66	106 x 86 x 124	495
30K-13	30	22	-	2460	86,9	147,6	400/50	G 1 1/4"	-	13	188	66	106 x 86 x 124	495
40K-8	40	30	-	4730	167	283,8	400/50	G 1 1/4"	-	8	116	67	106 x 86 x 124	515
40K-10	40	30	-	4210	148,7	252,6	400/50	G 1 1/4"	-	10	145	67	106 x 86 x 124	515
40K-13	40	30	-	3310	116,9	198,6	400/50	G 1 1/4"	-	13	188	67	106 x 86 x 124	515
50K-8	50	37	-	6130	216,5	367,8	400/50	G 1 1/2"	-	8	116	70	194 x 107 x 180	960
50K-10	50	37	-	5510	194,6	330,6	400/50	G 1 1/2"	-	10	145	70	194 x 107 x 180	960
50K-13	50	37	-	4250	150	255	400/50	G 1 1/2"	-	13	188	70	194 x 107 x 180	960
60K-8	60	45	-	7810	275,8	468,6	400/50	G 1 1/2"	-	8	116	70	194 x 107 x 180	1030
60K-10	60	45	-	6830	241,2	409,8	400/50	G 1 1/2"	-	10	145	70	194 x 107 x 180	1030
60K-13	60	45	-	5690	200,9	341,4	400/50	G 1 1/2"	-	13	188	70	194 x 107 x 180	1030
75K-8	75	55	-	8530	301,2	511,8	400/50	G 1 1/2"	-	8	116	70	194 x 107 x 180	1188
75K-10	75	55	-	7500	264,8	450	400/50	G 1 1/2"	-	10	145	70	194 x 107 x 180	1188
75K-13	75	55	-	7070	249,6	424,2	400/50	G 1 1/2"	-	13	188	70	194 x 107 x 180	1188

Dimensions : Length x Depth x Height