



Stealth oil free CS3

Type: **oil free traditional piston pump**
 Transmission type: **direct**
 Starting type: **direct drive**
 Range of power: **3÷9 Hp - 2,2÷6,6 kW**
 Range of pressure: **up to 7 Bar**
 Dew point (with membrane dryer): **-20 °C**
 (with adsorption dryer): **-40 °C**

Oil residual (ISO 8573-1): **class 1**
 F.A.D. (ISO 2017 annex C): **225÷750 L/min**
 Noise level: **max 72 L_{WA} (dB)**
 Motor efficiency: **IE2**
 Duty cycle: **S3 70%**



10 BAR VERSION
available on request



CS3-40/3



CS3-200/3x3

Stealth CS3 3÷9 Hp 7 Bar

Oil free compressors

Model	Pump Head	Tank	Air Displacement		Free Air Delivery*		Power Supply	Nominal Power		Revolutions	Max Pressure		Noise Level	Dimensions	Weight
STEALTH	type	Lt.	L/min	CFM	L/min	CFM	V/Hz	HP	kW	Rpm	Bar	Psi	L _{WA} (dB)	mm	Kg
CS3-40/3	CS3	40	360	12,6	250	8,8	230/50	3	2,2	1450	7	102	66	600 x 410 x 810	54
CS3-40/3T	CS3	40	360	12,6	250	8,8	400/50	3	2,2	1450	7	102	66	600 x 410 x 810	54
CS3-40/3E	CS3	40	360	12,6	225	8	230/50	3	2,2	1450	7	102	66	710 x 410 x 810	58
CS3-40/3TE	CS3	40	360	12,6	225	8	400/50	3	2,2	1450	7	102	66	710 x 410 x 810	58
CS3-100/3x2	CS3	90	720	25,2	500	17,7	230/50	3x2	2,2x2	1450	7	102	69	1100 x 600 x 820	113
CS3-100/3x2T	CS3	90	720	25,2	500	17,7	400/50	3x2	2,2x2	1450	7	102	69	1100 x 600 x 820	113
CS3-100/3x2E	CS3	90	720	25,2	450	15,9	230/50	3x2	2,2x2	1450	7	102	69	1100 x 630 x 820	118
CS3-100/3x2TE	CS3	90	720	25,2	450	15,9	400/50	3x2	2,2x2	1450	7	102	69	1100 x 630 x 820	118
CS3-200/3x3	CS3	200	1080	37,8	750	26,5	400/50	3x3	2,2x3	1450	7	102	72	1100 x 600 x 910	173
CS3-200/3x3E	CS3	200	1080	37,8	660	23,3	400/50	3x3	2,2x3	1450	7	102	72	1450 x 820 x 900	183

*L/min at 5 Bar / CFM at 70 Psi
 E = equipped with membrane dryer
 T = V 400 power supply

Dimension: Length x Depth x Height