

Silent lubricated

Type: **oil injected**

Transmission type: **direct**

Starting type: **direct drive**

Range of power: **0,25÷1,82 Hp - 0,18÷1,36 kW**

Range of pressure: **up to 7 Bar**

Air displacement (ISO 2017 annex C):

30÷200 L/min

Noise level: **max 45 L_{wa}(dB)**

Motor efficiency: **IE2**

Duty cycle: **S3 50%**

L02-1,5/0,25



L02-9/0,25

Mirage L02 0,25 Hp 7 Bar

Silent lubricated compressors

Model	Pump Head	Tank	Air Displacement		Power Supply	Nominal Power		Revolutions	Max Pressure		Noise Level	Dimensions	Weight
MIRAGE	type	Lt.	L/min	CFM	V/Hz	HP	kW	Rpm	Bar	Psi	L _{wa} (dB)	mm	Kg
L02-1,5/0,25	L02	1,5	30	1,1	230/50	0,25	0,18	2800	7	102	40	420 x 190 x 305	15
L02-6/0,25	L02	6	30	1,1	230/50	0,25	0,18	2800	7	102	40	370 x 330 x 360	16
L02-9/0,25	L02	9	30	1,1	230/50	0,25	0,18	2800	7	102	40	310 x 310 x 530	19

Dimension: Length x Depth x Height

L05-100/2













L05-24/1



Mirage L05 0,5÷2 Hp 7 Bar

Silent lubricated compressors

Model	 Pump Head	 Tank	 Air Displacement		 Power Supply	 Nominal Power		 Revolutions	 Max Pressure		 Noise Level	 Dimensions	 Weight
MIRAGE	type	Lt.	L/min	CFM	V/Hz	HP	kW	Rpm	Bar	Psi	L _{WA} (dB)	mm	Kg
L05-24/0,5	L05	24	50	1,8	230/50	0,5	0,37	2800	7	102	40	400 x 400 x 550	30
L05-24/1	L05	25	100	3,5	230/50	0,92	0,69	2800	7	102	40	580 x 320 x 580	43
L05-50/1,5	L05	50	150	5,3	230/50	1,37	1,02	2800	7	102	45	980 x 440 x 650	77
L05-100/2	L05	100	200	7,1	230/50	1,82	1,36	2800	7	102	45	1250 x 460 x 720	100

Dimension: Length x Depth x Height